

GAS DETECTOR

LNG, LPG GAS DETECTOR

Model : **SHT-4700**, SHT-4700D

Description

- ◆ TRANSMITTER TYPE (4~20mA)
- ◆ Model : **SHT-4700**, SHT-4700D

Feature

- The best gas measurement.
- The exact signal output.
- Explosion-proof certified – Korea(KOSHA), International(IECEx, ATEX)
- Due to the best program application, can measure combustible gases from low to high concentration.
- Stable performance and applying detection principle of proven durability.
- Compact design & Simple structure.
- One person possible calibration and maintenance.
- Approval on model by the Korea Fire Institute.
- Electromagnetic Interference Certification required.
- The gas detector installed in industries and explosion danger areas measures flammable gases in real time. The gas detector also provides 4~20mA standard output, connected to every controller for use. Functions of long-range solenoid valve opening/closing and warning light.



Specification

| | | | |
|-------------------------|--|-----------------------------------|---|
| Model | SHT-4700 : KOSHA certificate SHT-4700D : IECEx, ATEX certificate | Measuring gas | LNG, LPG |
| Measuring range | 0 ~ 100%(LEL) | Measuring method | Diffusion type, Catalytic combustion cell type |
| Measuring signal | 4~20mA | Response time | Less than 20sec |
| Accuracy | ±3% / Full scale | Operating Temp' / Humi' | -20°C ~ +60°C / 95% RH (Non-condensing) |
| Operating power | 24V.DC | Consumption electric power | 1.45W (2.4W During normal operation) |
| Cable/Distance | F-CVVS(Shield) 1.5sq × 3wire /Max 2,500M | Conduit connection | 1/2(16MM) PF, NPT |
| Mounting type | Wall mounting | Approval | Ex d IIB T4(KOSHA), Ⓔ II2G Ex IIB T4 Gb(IECEx, ATEX) |
| Dimension | 95(W) × 100(H) × 71(D) mm | Weight | 0.58Kgs |

Dimension

